

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): A method for monitoring the status of an electronic network, said method comprising:

executing a first program a plurality of times on at least one portion of said electronic network, wherein said first program measures a parameter or said network;

receiving first data resulting from the execution of said first program;

analyzing said first data, wherein to determine if the difference of said at least two measurements exceeds a preselected amount, said at least one portion of said network is not operating within a preselected specification;

executing a second program on said at least one portion of said electronic network if the analysis of said first data indicates that said at least one portion of said electronic network is not operating within said preselected specification;

receiving second data resulting from the execution of said second program;

and

analyzing said first data and second data to determine the cause of said at least one portion of said network not operating within said preselected specification.

Claim 2 (original): The method of claim 1, wherein said executing a first program comprises measuring the latency associated with said at least one portion of said electronic network.

Claim 3 (original): The method of claim 1, wherein said at least one portion of said network has a connector associated therewith, said connector storing a management information base, and wherein said executing a first program comprises measuring data stored in said management information base.

Claim 4 (cancelled)

Claim 5 (currently amended): The method of claim 1, wherein said first program stores correlations between previous network conditions and previous network problems, and wherein said executing a first program comprises comparing present network conditions to stored network conditions and determining whether a network problem based at least in part on the comparison.

Claim 6 (original): The method of claim 1, wherein said executing said first program comprises running at least one trace route routine on said at least one portion of said network, said trace route routine measuring the latency of said at least one portion of said network.

Claim 7 (cancelled)

Claim 8 (original): The method of claim 1 and further comprising displaying a graphical user interface representative of said network, said graphical user interface indicating said portion of said network not operating within said preselected specification.

Claim 9 (original): The method of claim 8, wherein said graphical user interface further displays information relating to at least one cause of said network not operating within said preselected specification.

Claim 10 (currently amended): A device for evaluating the operational status of an electronic network, said device comprising a computer operatively connected to said network, said computer comprising a computer-readable medium having instructions for operating said computer and evaluating said network by:

executing a first program a plurality of times on at least one portion of said electronic network, wherein said first program measures a parameter or said network;

receiving first data resulting from the execution of said first program;
analyzing said first data, wherein if the difference of said at least two
measurements exceeds a preselected amount, said at least one portion of said
network is not operating within a preselected specification;

executing a second program on said at least one portion of said electronic network if the analysis of said first data indicates that said at least one portion of said electronic network is not operating within said preselected specification;

receiving second data resulting from the execution of said second program;
and

analyzing said first data and second data to determine the cause of said at least one portion of said network not operating within said preselected specification.

Claim 11 (original): The device of claim 10, wherein said executing a first program comprises measuring the latency associated with said at least one portion of said electronic network.

Claim 12 (previously presented): The device of claim 10, wherein said at least one portion of said network has a connector associated therewith, said connector storing a management information base, and wherein said executing a first program comprises measuring data stored in said management information base.

Claim 13 (cancelled)

Claim 14 (previously presented): The device of claim 10, wherein said first program stores correlations between previous network conditions and previous network problems, and wherein said executing a first program comprises comparing present network conditions to stored network conditions and determining a network problem based at least in part on the comparison.

Claim 15 (previously presented): The device of claim 10, wherein said executing said first program comprises running at least one trace route routine on

said at least one portion of said network, said trace route routine measuring the latency of said at least one portion of said network.

Claim 16 (cancelled)

Claim 17 (previously presented): The device of claim 10 and further comprising displaying a graphical user interface representative of said network, said graphical user interface indicating said portion of said network not operating within said preselected specification.

Claim 18 (original): The method of claim 17, wherein said graphical user interface further displays information relating to at least one cause of said network not operating within said preselected specification.

19 (currently amended): A device for monitoring the status of an electronic network, said device comprising:

first diagnostic means for executing a first diagnostic program a plurality of times on at least one portion of said electronic network, said first diagnostic program generating first data measurements representative of the status of said at least one portion of said electronic network;

first analysis means for analyzing said first data, wherein if the difference of at least two measurements exceeds a preselected amount, said at least one portion of said network is not operating within a preselected specification;

second diagnostic means for executing a second diagnostic program on at least one portion of said electronic network if said first analysis means determines that said at least one portion of said electronic network is not operating within a preselected specification, said second diagnostic program generating second data representative of the status of said at least one portion of said network; and

second analysis means for analyzing said first data and said second data, said second analysis means generating an indication representative of the cause of said at least one portion of said electronic network not operating within said preselected specification.